



Separation Solution

Triumphs

Refining a Massachusetts city's combined sewer overflow (CSO) relief plan using hydraulic modeling

By Gregory Heath, David Minard, Donald Walker, Amanda Roberts & Joshua Schimmel



The city of Springfield, the largest community in southwestern Massachusetts, needed to protect receiving waters from CSO discharges.

With the aid of InfoWorks CS, the Springfield Water and Sewer Commission (SWSC) in southwestern Massachusetts has been able to find a cost-effective and environmentally sustainable alternative to a proposed CSO relief project.

Springfield is the largest community and major urban center in southwestern Massachusetts. As in many cities with combined sewer systems, discharges from CSOs have polluted receiving waters—a problem which resulted in inceptor sewers being built while excess flows during wet weather still discharged via the CSOs.

The SWSC and city of Springfield have undertaken a number of CSO control and mitigation activities, including a regional CSO study. The long-term control plan, drawn up in 2000, sets out a range of projects in a number of phases that have to be implemented to meet an administrative order schedule negotiated with the Massachusetts Department of Environmental Protection (DEP) and the U.S. Environmental Protection Agency (EPA).

The SWSC decided to update baseline conditions in the project area ahead of ongoing works, and as a result, it defined a series of projects that aligned better with the goal of upgrading its collection system infrastructure.

The commission's Clinton Street screening and disinfection facility project—the first one called for in the long-term plan—is an example of this approach. Following this work, discharges from one CSO would cease and those at another be eliminated for storms up to and including the two-year, 24-hour storm. Construction was due to begin in 2009.

InfoWorks Model

The InfoWorks model was updated with all collected field information, and the level of detail was expanded to include pipes 24 in. or more in diameter. Once updated and

expanded, the model was recalibrated using the 32 flowmeters deployed for the project.


After this, the model was used to define the baseline conditions for designing the Clinton Street facility. The difference in total discharge volume predictions was minimal, but it was seen as clearly appropriate to increase the level of detail, accuracy

and confidence in the model to support the design of the facility and the assessment of alternatives.

Modeling Alternatives

Upon completing the model calibration and update of baseline conditions, a review of hydraulic profiles and flow conditions in the interceptor and CSO tributary trunk

ECO-INLET® STORM WATER DRAIN COVERS




(Patent #7,160,048)

The new steel Eco-Inlet® Storm Water Drain Cover provides effective storm water management, drainage and flood plain protection. Our patented Eco-Inlet® Storm Water Drain Covers prevent litter, solid waste and other floatables from entering and polluting our water supplies, in accordance with the EPA regulations.

NEW SUNBURST ECO-INLET FEATURES & BENEFITS

- Mounts to the existing catch basin curb heads in minutes using a tamper proof bolt.
- Replacement cost savings of nearly three times over alternative products.
- The new Sunburst design fits multiple curb head sizes, including 6", 8", 10" and more. Any curb inlet width can be accommodated with a standard or custom Eco-Inlet®.
- The steel Eco-Inlet has been plow-tested and Engineer approved.
- All sizes comply with the 2" maximum code specification.
- It is made from rigid Cor-Ten® steel, which produces a light layer of brown oxidation to form a strong, durable cover that protects against deterioration.
- The compression clamps are designed to fit into any of the fifteen flow holes allowing it to fit securely onto many different styles of curb inlets.
- Each Eco-Inlet contains four Cor-Ten® steel compression clamps and four low profile tamper-resistant bolts. Four stainless steel conical washers protect the bolt heads and deflect direct impact from snowplow blades.
- The notched end clamp slots, support feet, and chamfered-edges dramatically reduce potential damage from impact.
- NJDOT APPROVED



LMT Mercer Group, Inc. P: 1.888.570.5252
F: 1.609.989.1199
690 Puritan Avenue E: orders@lmtproducts.com
Lawrenceville, NJ 08648 W: www.lmtproducts.com

sewers was undertaken. Based on the profiles and system storage, as well as input from the SWSC, a list of alternatives was identified for further evaluation.

A number of options were rejected because of relatively modest reductions in discharge or because modeling found them to be complex and costly. Because of the storm

water separation already found, it was decided to re-examine the previously rejected option of sewer separation as an alternative.

The model was used to assess the feasibility of closing outfalls from two regulators by comparing peak hydraulic grade lines and flooding against baseline conditions. The modeling showed complex results

from the proposed changes, with improvements for some aspects and worse conditions for others.

The model was then used to optimize performance of this alternative. By changing various factors, the peak hydraulic grade lines were brought down below baseline conditions. Now a very high level of CSO control could be achieved at one outfall. Additional simulations showed that the outfall could be closed in the future if the next downstream area tributary to the interceptor was separated.

BEFORE
AFTER

Algae Control Without Chemicals!

NEW! Solar Available

Environmentally safe SonicSolutions® controls algae in ponds, pools, lakes, and reservoirs by using ultrasonic waves to kill algae. Unlike many chemical controls, SonicSolutions® won't harm fish, plants, or other aquatic life. A single unit can provide coverage for up to three acres or can be used in combination for larger applications. Call today for more information about the SonicSolutions® algae control system.

Ask us about our
3-Month Rental Demo!

SONIC SOLUTIONS[®] LLC

Call us for a quote, toll free: **1-866-KO-ALGAE** (1-866-562-5423)
77B West Street • West Hatfield, MA 01088 • www.sonicsolutionsllc.com

Tanks — Lakes — Ponds — Pools — Lagoons — Reservoirs

Original Plan vs. Alternative

In terms of all the factors—reductions in surcharges and flooding, CSO activation and volume, *E. coli* loading and receiving water impacts—the alternative was found to perform as well or better than the Clinton Street facility. This option will allow the SWSC to have more flexibility to implement further CSO controls along the Connecticut River while staying within the long-term control plan.

Both the facility and the alternative plan costs were found to be nearly the same, though the facility would have additional operation and maintenance overheads. The alternative could also be designed and constructed in time to meet the anticipated 2011 completion date.

Following these evaluations, SWSC sought and obtained approval from the DEP and EPA to substitute the sewer separation project for the previous screening and disinfection project. SWS

This article is based on a paper by Gregory Heath, David Minard and Donald Walker, Metcalf & Eddy, and Amanda Roberts and Joshua Schimmel, Springfield Water and Sewer Commission. For more information, visit www.wallingfordsoftware.com or e-mail sales@wallingfordsoftware.com.

Learn More

For more information related to this article, visit www.estormwater.com/lm.cfm/st030806

For more information, write in 5006 on this issue's Reader Service Card.

Write in 8007